Designation	Body*	Air Orifice	Pre-Mix Orifice	Gas Tube*	Tube Adapter	Inlet Flange*	Gasket*	Exit Tile*
4020-6-LP/4	4-20508-1			4-16620-6	4-20466-1	8765-6-C (2-2310-14)	4-5371-2	4-20513-1
4020-6-LP/5	4-20508-1			4-16620-6	4-20466-1	8765-6-C (2-2310-14)	4-5371-2	4-20513-2
4020-7-LP/6	4-20508-2			4-16620-7	4-20466-2	2-2310-7	4-5371-3	4-20513-3


 $<sup>^{</sup>st}$  These parts are also used on the -6 and -7" HP" versions

Designation	Body†	Air Orifice	Pre-Mix Orifice	Gas Tube†	Tube Adapter	Inlet Flange†	Gasket†	Exit Tile†
4020-6-HP/4	4-20508-1	4-16621-5	4-16620-5	4-16620-6		8765-6-C (2-2310-14)	4-5371-2	4-20513-1
4020-6-HP/5	4-20508-1	4-16621-5	4-16520-5	4-16620-6		8765-6-C (2-2310-14)	4-5371-2	4-20513-2
4020-7-HP/6	4-20508-2	4-16621-6	4-16520-6	4-16620-7		2-2310-7	4-5371-3	4-20513-3


 $<sup>\</sup>dagger$  These parts are also used on the -6 and -7" LP" versions

Standard 10mm spark plug (R240-2465) is provided with each 4020

- 1. Body
- 2. Air Orifice
- 3. Pre-Mix Orifice
- 4. Gas Tube
- 5. Tube Adapter
- 6. Inlet Flange
- 7. Gasket
- 8. Exit Tile



4020-6-LP/# and -7-LP#



4020-6-HP/# and -7-HP#

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

## CONTACT

fna.sales@fivesgroup.com T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc. 4455 East 71st Street - Cleveland, OH 44105 - USA www.fivesgroup.com

