

# Part Numbers | 4422 Gas Burners

## Example 4422 Catalog Numbers

examples are given from smallest to largest available burner sizes

### Standard Burner

4422-2-BO	through	4422-8-ABO	burner only
4422-2	through	4422-8-A	burner complete w/9" tile

### Standard Burner With Tile Jacket

4422-2-LC	through	4422-8-ALC	burner complete w/9" tile and steel jacket
4422-2-L4	through	4422-8-AL4	burner complete w/9" tile and 304 SST jacket
4422-2-L9	through	4422-8-AL9	burner complete w/9" tile and 309 SST jacket

### Burner With Double-Boss Body

4422D-2-BO	through	4422D-6-BBO	burner only w/double-boss body
4422D-2	through	4422D-6-B	burner complete w/9" tile and double boss body
4422D-2-LC	through	4422D-6-BLC	burner complete w/9" tile, double-boss body and steel jacket
4422D-2-L4	through	4422D-6-BL4	burner complete w/9" tile, double-boss body and 304 SST jacket
4422D-2-L9	through	4422D-6-BL9	burner complete w/9" tile, double-boss body and 309 SST jacket

### Burner With Hinged Burner Body

4422HR-2-BO	through	4422HR-8-ABO	burner only w/right-hand hinged body when main air is at 12 o'clock
4422HL-2-BO	through	4422HL-8-ABO	burner only w/left-hand hinged body when main air is at 12 o'clock
4422HR-2	through	4422HR-8-A	burner complete w/9" tile and right-hand hinged body when main air is at 12 o'clock
4422HL-2	through	4422HL-8-A	burner complete w/9" tile and left-hand hinged body when main air is at 12 o'clock
4422HR-2-LC	through	4422HR-8-ALC	burner complete w/9" tile and steel jacket with right-hand hinged body when main air is at 12 o'clock
4422HL-2-LC	through	4422HL-8-ALC	burner complete w/9" tile and steel jacket with left-hand hinged body when main air is at 12 o'clock
4422HR-2-L4	through	4422HR-8-AL4	burner complete w/9" tile and 304 SST jacket with right-hand hinged body when main air is at 12 o'clock
4422HL-2-L4	through	4422HL-8-AL4	burner complete w/9" tile and 304 SST jacket with left-hand hinged body when main air is at 12 o'clock
4422HR-2-L9	through	4422HR-2-AL9	burner complete w/9" tile and 309 SST jacket with right-hand hinged body when main air is at 12 o'clock
4422HL-2-L9	through	4422HL-2-AL9	burner complete w/9" tile and 309 SST jacket with left-hand hinged body when main air is at 12 o'clock

### Fiber Wall Mounting Burners

4422-2-Z	through	4422-8-AZ	burner complete w/"Z" dimension (2" to 9" round)
4422D-2-Z	through	4422D-6-BZ	burner complete w/double-boss body and "Z" dimension (2" to 9" round)

### Flangeless Burners

4422-2-FM	through	4422-8-AFM	burner complete w/9" tile and flangeless mounting
4422D-2-FM	through	4422D-6-BFM	burner complete w/9" tile, double-boss body and flangeless mounting

**WARNING:** Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

## CONTACT

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

**Fives North American Combustion, Inc.**  
4455 East 71st Street - Cleveland, OH 44105 - USA  
[www.fivesgroup.com](http://www.fivesgroup.com)



**fives**  
Industry can do it