



Low NOx Flat Flame™ Burner Tiles

Sheet 4832-4

All tiles are grooved except for tapered and fiber wall tiles.

4832 (Wall)

	3000°F castable		3200°F castable	
Burner size/shape	9" deep	13" deep	9" deep	13" deep
4832-2, -3, -4 Standard tile				
Round	4-8678-1	4-8678-7	4-8678-3	4-8678-9
Square	4-8686-1	4-8686-7	4-8686-3	4-8686-9
Square tapered	4-8688-1	4-8688-7	4-8688-3	4-8688-9
Fiber wall tile Round with liner Square with liner	4-6982-1 4-7401-1	4-6982-7 4-7401-7	4-6982-3 4-7401-3	4-6982-9 4-7401-9
4832-5 , -6 , -7 Standard tile				
Round	4-8678-2	4-8678-8	4-8678-4	4-8678-10
Square	4-8686-2	4-8686-8	4-8686-4	4-8686-10
Square tapered	4-8688-2	4-8688-8	4-8688-4	4-8688-10
Fiber wall tile*				
Round with liner	4-6982-2	4-6982-8	4-6982-4	4-6982-10
Square with liner	4-7401-2	4-7401-8	4-7401-4	4-7401-10

^{*} suitable for wall installation only

4832 (Roof) - for use in fiber and hard refractory roofs

	3200°F castable		
Burner size/shape	9" deep	13" deep	
4832-2 , -3 , -4 Square tile	OB4-0402-5	OB4-0402-7	
4832-5 , -6 , -7 Square tile	OB4-0402-6	OB4-0402-8	
4832-8-A, -8-B Square tile Round tile	OC4-0975-1 OC4-2512-1	OC4-0975-2 OC4-2512-2	

NOTE:

Consult Fives North American Combustion, Inc. for delivery of 13" deep tiles--tooling not yet available for all configurations.

ved | Sheet 4832-4 05/16 WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com T +1 800 626 3477 - F +1 216 373 4237

