



North American Low NOxFlat Flame™ Burners Tile and Mounting Assemblies

Sheet 4832-5

All tiles have externally grooved sides except the tapered and fiber wall versions.

4832 (Wall)

Burner size/shape	3000 F castable		3200 F castable	
	9" deep	13" deep	9" deep	13" deep
4832-2, -3, -4				
Standard tile				
Round	4-28571-1	4-28571-7	4-28571-3	4-28571-9
Square	4-28570-1	4-28570-7	4-28570-3	4-28570-9
Square tapered	4-28569-1	4-28569-7	4-28569-3	4-28569-9
Fiber wall tile	See page 2		See page 2	
4832-5, -6, -7				
Standard tile				
Round	4-28571-2	4-28571-8	4-28571-4	4-28571-10
Square	4-28570-2	4-28570-8	4-28570-4	4-28570-10
Square tapered	4-28569-2	4-28569-8	4-28569-4	4-28569-10
Fiber wall tile♦	See page 2		See page 2	
4832-8-A, -8 -B				
Round, flanged*			4-28629-1	4-28625-2

* See Sheet 4832-6, page 2

♦Suitable for wall installation only

4832 (Roof) - for use in fiber and hard refractory roofs

Burner size/shape	3200°F castable	
	9" deep	13" deep
4832-2, -3, -4 (Square tile)	4-28626-1	4-28626-3
4832-5, -6, -7 (Square tile)	4-28626-2	4-28626-4
4832-8-A, -8-B (Square tile)	4-28627-1	4-28627-2
(Round tile)	4-28628-1	4-28628-2

NOTE:

Consult Fives North American Combustion, Inc. for delivery of 13" deep tiles--tooling not yet available for all configurations.