

| Mounting & Tile Assemblies Standard | for Burner Complete w/9" Tile | | | | | | | |
|-------------------------------------|---|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Mounting & Tile Assy. ④ | 3-6668-1 | 3-6668-1 | 3-6668-1 | 3-6668-1 | 3-6668-1 | 3-6668-2 | 3-6668-2 | 3-6668-2 |
| LC Series | for Burner Complete w/9" Tile and Steel Jacket | | | | | | | |
| Mounting & Tile Assy. ④ | 3-6668-3 | 3-6668-3 | 3-6668-3 | 3-6668-3 | 3-6668-3 | 3-6668-4 | 3-6668-4 | 3-6668-4 |
| Tile & Jacket Assembly ⑤ | 4-21583-1 | 4-21583-1 | 4-21583-1 | 4-21583-1 | 4-21583-1 | 4-21583-2 | 4-21583-2 | 4-21583-2 |
| Jacket | 4-5377-3 | 4-5377-3 | 4-5377-3 | 4-5377-3 | 4-5377-3 | 4-5378-3 | 4-5378-3 | 4-5378-3 |
| L4 Series | for Burner Complete w/9" Tile and 304 SST Jacket | | | | | | | |
| Mounting & Tile Assy. ④ | 3-6668-5 | 3-6668-5 | 3-6668-5 | 3-6668-5 | 3-6668-5 | 3-6668-6 | 3-6668-6 | 3-6668-6 |
| Tile & Jacket Assembly ⑤ | 4-21583-3 | 4-21583-3 | 4-21583-3 | 4-21583-3 | 4-21583-3 | 4-21583-4 | 4-21583-4 | 4-21583-4 |
| Jacket | 4-5377-4 | 4-5377-4 | 4-5377-4 | 4-5377-4 | 4-5377-4 | 4-5378-4 | 4-5378-4 | 4-5378-4 |
| L9 Series | for Burner Complete w/9" Tile and 309 SST Jacket | | | | | | | |
| Mounting & Tile Assy. ④ | 3-6668-7 | 3-6668-7 | 3-6668-7 | 3-6668-7 | 3-6668-7 | 3-6668-8 | 3-6668-8 | 3-6668-8 |
| Tile & Jacket Assembly ⑤ | 4-21583-5 | 4-21583-5 | 4-21583-5 | 4-21583-5 | 4-21583-5 | 4-21583-6 | 4-21583-6 | 4-21583-6 |
| Jacket | 4-5377-6 | 4-5377-6 | 4-5377-6 | 4-5377-6 | 4-5377-6 | 4-5378-5 | 4-5378-5 | 4-5378-5 |

① Includes 3-3638-1 Adapter

② Gas Tube and Gas Connection are integral on 6422-7-A, -7-B, and -8-A

③ Extra cost option--not part of standard burner assembly, and must be ordered separately.

④ Includes complete mounting, tile, jacket and retainer assembly.

⑤ Includes tile and jacket only.

Order Must Specify: **1-Part Number** **2-Part Name** **3-Burner Designation**

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it