DIMENSIONS in inches









When ordering, specify choice of options as follows:

(P) for spark ignited pilot

OPTIONS

- (Y) for 45° air connection
- (T) for 90° air connection
- (F) for flanged air connection
- (SW) slip-on or welding air connection

Example: 6570-12-PTF Burner complete 1813-01 Sensitrol Oil Valve

DIMENSIONS SHOWN ARE SUBJECT TO CHANGE. PLEASE OBTAIN CERTIFIED PRINTS FROM FIVES NORTH AMERICAN COMBUSITON, INC. IF SPACE LIMITATIONS OR OTHER CONSIDERATIONS MAKE EXACT DIMENSION(S) CRITICAL.

4570 HiVAM™s for gas only have the same dimensions (except for "N" and "C", which do not apply) and practically the same weights as 6570 HiVAMs since the gas burners also have an "atomizing air" connection for greater flame stability.

Burner designation	dimensions in inches													Recommended Sensitrol™ Oil Valve	Approx. net weight Ib		
6570-9	8	2½	3⁄8	16¼6	15 ¹³ ⁄16	3¾	29 ¹⁵ ⁄16	7%	8	115⁄16	15 ¹³ ⁄16	237⁄8	4½	85⁄8	3⁄8	1813-02-D	125
6570-12	12	3	1⁄2	19 ¹³ ⁄16	215⁄16	4¾	42 ¹³ ⁄32	8	12	1427⁄32	23 ¹³ ⁄16	345⁄8	5½6	113⁄4	1⁄2	1813-01	200

D Optional (recommended) Sensitrol Oil Valve is not included as part of the burner assembly, and must be ordered separately.

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc. 4455 East 71st Street - Cleveland, OH 44105 - USA www.fivesgroup.com

