



DIMENSIONS SHOWN ARE SUBJECT TO CHANGE. PLEASE OBTAIN CERTIFIED PRINTS FROM FIVES NORTH AMERICAN COMBUSTION, INC. IF SPACE LIMITATIONS OR OTHER CONSIDERATIONS MAKE EXACT DIMENSION(S) CRITICAL.

All dimensions are in inches. Dimensions shown apply only to blowers with TS-frame motors. Consult Fives North American for dimensions of blowers with other motors.

Blower number ★	A	B	C	D	F	G	H	J	K	L	M	P	Q	R	S	U
2310-39/1-T50D	24	9¾	19	11⅞	39¾	35	13¾	35¾	¾	10⅞	11⅞	17¼	20⅞	23¾	22	46½
2310-39/1-T60D	24	10⅞	20	11⅞	38⅞	35	13¼	36⅞	¾	11⅞	12⅞	18⅞	21⅞	23¾	24	47⅞
2310-39/1-T75D	24	10½	20	12⅞	38¾	35	14⅞	35⅞	¾	11⅞	12⅞	18⅞	22⅞	24⅞	24	49⅞
2310-39/1-T100D	26	11⅞	22⅞	12⅞	39½	35	14⅞	36	¾	12⅞	14	20⅞	23⅞	26⅞	26	53⅞
2310-39/1-T125D	30	11½	26	13⅞	41¼	35	15½	36¼	¾	13⅞	15	20⅞	24⅞	27½	26	56⅞
2312-34/1-T20D	16	5	16⅞	6⅞	32⅞	35	11⅞	30	¾	8¾	9⅞	14½	16¾	18⅞	14	29⅞
2312-34/1-T25D	16	5¼	18⅞	7⅞	32¾	35	11⅞	30	¾	9⅞	10⅞	14½	16¾	18⅞	14	33⅞
2312-34/1-T30D	20	6⅞	18⅞	8⅞	33¾	35	15⅞	30½	¾	9⅞	10⅞	16⅞	20⅞	23⅞	16	37⅞
2312-34/1-T40D	20	7⅞	19	8⅞	33¼	35	14⅞	30½	¾	10⅞	11⅞	16⅞	20⅞	23⅞	16	39⅞
2312-37/1-T50D	22	7⅞	19	9⅞	38¾	35	15⅞	35½	¾	10⅞	11⅞	17⅞	21⅞	25⅞	18	41⅞
2312-37/1-T60D	24	7⅞	20	9⅞	39⅞	35	16⅞	35⅞	¾	11⅞	12⅞	17¾	21⅞	25⅞	18	42⅞
2312-37/1-T75D	24	7⅞	20	9⅞	38⅞	35	16⅞	35⅞	¾	11⅞	12⅞	18⅞	22⅞	26⅞	18	44⅞
2316-37/1-T40D	18	5½	19	7⅞	38¼	35	13⅞	35¼	¾	10⅞	11⅞	16⅞	19	21⅞	16	36⅞
2316-37/1-T50D	18	5⅞	19	7⅞	38	35	13⅞	35¼	¾	10⅞	11⅞	16⅞	19	21⅞	16	38¼
2316-37/1-T60D	24	7½	20	9⅞	39¾	35	16⅞	35¾	¾	11⅞	12⅞	18⅞	22⅞	26⅞	18	42⅞
2316-37/1-T75D	24	8	20½	9⅞	38⅞	35	16⅞	35⅞	¾	11⅞	12⅞	18⅞	22⅞	26⅞	18	44⅞
2316-37/1-T100D	24	8¼	22⅞	10⅞	38⅞	35	17⅞	35⅞	¾	12⅞	14	19⅞	23⅞	27⅞	20	47⅞
2320-37/1-T60D	20	6⅞	20	7⅞	38⅞	35	15⅞	35⅞	¾	11⅞	12⅞	18	20⅞	23⅞	18	33⅞
2320-37/1-T75D	20	6⅞	20	7⅞	38½	35	15⅞	35½	¾	11⅞	12⅞	18⅞	21¼	24⅞	18	40⅞
2320-37/1-T100D	22	6½	22⅞	8⅞	39½	35	15⅞	35¾	¾	12⅞	14	18⅞	21¼	24⅞	18	43⅞
2320-37/1-T125D	26	8⅞	26	10¼	39¾	35	19⅞	36	¾	13⅞	15	20⅞	25⅞	30⅞	20	50⅞
2320-37/1-T150D	26	8⅞	26	10⅞	39⅞	35	19¼	35⅞	¾	13⅞	15	21⅞	26	30¾	22	53⅞
2320-39/1-T200D	30	9⅞	26	11⅞	41	35	20	36½	¾	13⅞	15	22½	27½	32½	22	48⅞
2320-39/1-T250D	30	12⅞	26	14⅞	40½	35	17¾	37	¾	13⅞	15	23¾	27⅞	31¼	30	57⅞
2324-37/1-T75D	20	5¼	20	7⅞	39	35	13⅞	35½	¾	11⅞	12⅞	18¼	20⅞	21⅞	16	38⅞
2324-37/1-T100D	24	6⅞	22⅞	8⅞	39¾	35	16¼	35½	¾	12⅞	14	19⅞	22⅞	25¾	18	44⅞
2324-37/1-T125D	24	6¾	26	8⅞	40⅞	35	16⅞	35⅞	¾	13⅞	15	19⅞	23⅞	26⅞	18	47⅞
2324-37/1-T150D	24	8	26	9⅞	38¾	35	15⅞	36¼	¾	13⅞	15	20⅞	23⅞	26⅞	22	51⅞
2332-37/1-T75D	20	4⅞	20½	6⅞	38⅞	35	16⅞	35⅞	¾	11⅞	12⅞	20⅞	22⅞	24⅞	16	38
2332-37/1-T100D	24	6⅞	22⅞	7⅞	40⅞	35	14⅞	36⅞	¾	12⅞	14	20⅞	22⅞	24⅞	16	43⅞
2332-37/1-T125D	24	6⅞	26	8⅞	40½	35	14½	36½	¾	13⅞	15	20⅞	22⅞	24½	16	46½
2332-37/1-T150D	24	6⅞	26	8⅞	40½	35	14⅞	37¾	¾	13⅞	15	20⅞	23⅞	24⅞	18	49¼

★ Explanation of designation: 2312-34/1-T40D means Series 2300, 12 psi pressure, inner housing no. 34, 1 stage, 40 hp motor, direct drive.

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com
T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com

