

Blower Designation	Impeller Part #	Slip-On Discharge Adapter	Seal Kit #*	Shaft Seal Retainer	Shaft Seal	Heat Slinger	Heat Shield	Discharge Flange Gasket	Stationary Vane Assy (for 2 stage)	# of feet†
2620-33/1-25/25	1-1399-9SC	1-1627-3	2600FS-33/1	1-3171-3	1-3172-3	1-3289-4	1-3175-2	1-3174-9		8
2620-33/1-30/30	1-1399-9SC	1-1627-3	2600FS-33/1	1-3171-3	1-3172-3	1-3289-4	1-3175-2	1-3174-9		8
2620-33/1-40/40	1-1399-8SC	1-1626-3	2600FS-33/1	1-3171-4	1-3172-4	1-3289-5	1-3175-2	1-3174-9		8
2620-33/1-50/50	1-1399-8SC	1-1626-3	2600FS-33/1	1-3171-4	1-3172-4	1-3289-5	1-3175-2	1-3174-9		8
2620-33/1-60/60	1-1399-13SC	1-1626-3	2600FS-33/1	1-3171-7	1-3172-7	1-3289-6	1-3175-2	1-3174-9		8
2624-19/2-3/3	1-0684-22SC	1-1783-4	2600FS-19/2	1-3171-5	1-3172-5	1-3289-1	1-3175-1	1-3174-5	1-3280-2	14
2624-26/2-5/5	1-3139-10SC	1-1783-5	2600FS-26/2	1-3171-5	1-3172-5	1-3289-1	1-3175-1	1-3174-6	1-3280-6	16
2624-26/2-7/7.5	1-3139-11SC	1-1783-5	2600FS-26/2	1-3171-6	1-3172-6	1-3289-2	1-3175-1	1-3174-6	1-3280-6	16
2624-33/1-25/25	1-1378-7SC	1-1627-3	2600FS-33/1	1-3171-3	1-3172-3	1-3289-4	1-3175-2	1-3174-9		8
2624-33/1-30/30	1-1378-7SC	1-1627-3	2600FS-33/1	1-3171-3	1-3172-3	1-3289-4	1-3175-2	1-3174-9		8
2624-33/1-40/40	1-1378-8SC	1-1627-3	2600FS-33/1	1-3171-4	1-3172-4	1-3289-5	1-3175-2	1-3174-9		8
2624-33/1-50/50	1-1450-8SC	1-1626-3	2600FS-33/1	1-3171-4	1-3172-4	1-3289-5	1-3175-2	1-3174-9		14
2624-33/1-60/60	1-1450-9SC	1-1626-3	2600FS-33/1	1-3171-7	1-3172-7	1-3289-6	1-3175-2	1-3174-9		14
2632-21/2-25/25	1-0520-6SC	1-1630-3	2600FS-21/2	1-3171-3	1-3172-3	1-3289-4	1-3175-1	1-3174-2	1-3280-3	22
2632-33/2-50/50	1-1917-6SC	1-1627-3	2600FS-33/2	1-3171-4	1-3172-4	1-3289-5	1-3175-2	1-3174-9	1-3280-9	36
2644-21/2-50/50	1-1358-4SC	1-1630-3	2600FS-21/2	1-3171-4	1-3172-4	1-3289-5	1-3175-1	1-3174-2	1-3280-4	22

\*Seal kits to include shaft seal, seal retainer, and case seals.  
†R540-0370 joint sealant ¼" diameter Gore-tex.

**WARNING:** Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

## CONTACT

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

**Fives North American Combustion, Inc.**  
4455 East 71st Street - Cleveland, OH 44105 - USA  
[www.fivesgroup.com](http://www.fivesgroup.com)



**fives**  
Industry can do it