

Blower designation	at 70°F, cfm at 100% of motor rating	TEFC Motor			Discharge pipe size inches
		designation		W × D × L	
2624-19/2-3/3	210	T3.0-D36TIK9.7C	Keyway	¼ × ⅛ × 5½	7
2624-26/2-5/5	370	T5.0-D36TIK9.7C	Keyway	¼ × ⅛ × 5½	8
2624-26/2-7/7.5	600	T7.5-D36TIK9.7C	Keyway	⅝ × ⅝ <sub>32</sub> × 6 <sup>5</sup> / <sub>8</sub>	8
2624-33/1-25/25	2400	T25-D36TIK12.0C	Keyway	½ × ¼ × 4½	12
2624-33/1-30/30	2800	T30-D36TIK12.0C	Keyway	½ × ¼ × 4½	12
2624-33/1-40/40	3700	T40-D36TIK12.0C	Keyway	½ × ¼ × 4½	12
2624-33/1-50/50	5200	T50-D36TIK12.0C	Keyway	½ × ¼ × 4½	14
2624-33/1-60/60	6200	T60-D36TIK12.0C	Keyway	⅝ × ⅝ <sub>16</sub> × 4 <sup>5</sup> / <sub>8</sub>	14
2632-21/2-25/25	1500	T25-D36TIK15.0C	Keyway	½ × ¼ × 10	9
2632-33/2-50/50	3200	T50-D36TIK14.0C	Keyway	½ × ¼ × 8	12
2644-21/2-50/50	2500	T50-D36TIK15.0C	Keyway	½ × ¼ × 10	9

2600 Series hot air blowers are quoted, sold, and produced with motors furnished by North American. For applications that require severe duty, or high efficiency severe duty motors, please contact North American.

**WARNING:** Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

**CONTACT**

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

**Fives North American Combustion, Inc.**  
4455 East 71st Street - Cleveland, OH 44105 - USA  
[www.fivesgroup.com](http://www.fivesgroup.com)



**fives**  
Industry can do it