

Chart | Panel Filters/Silencers

Blower designation	Filter designation †	Filter-Silencer designation †	dimensions in inches			Filter approximate weight lb	Filter-Silencer approximate weight lb
			E	G	R		
2320-33/1- -- 50	2921-1202-6/33	2941-1202-6/33	39 ⁷ / ₈	34 ¹ / ₂	43	270	320
2320-41/1- -- 50	2921-1602-6/41	2941-1602-6/41	50 ³ / ₄	38	43	310	390
2320-41/1- -- 60	2921-1602-8/41	2941-1602-8/41	50 ³ / ₄	38	43	330	410
2324-33/1- -- 50	2921-1402-6/33	2941-1402-6/33	41 ⁵ / ₈	34 ¹ / ₂	43	270	340
2324-41/1- -- 60	2921-1602-8/41	2941-1602-8/41	50 ³ / ₄	38	43	330	410
2324-33/1- -- 60	2921-1402-8/33	2941-1402-8/33	41 ⁵ / ₈	34 ¹ / ₂	43	290	360
2324-41/1- -- 75	2921-1602-8/41	2941-1602-8/41	50 ³ / ₄	38	43	330	410
2332-41/2- -- 100	2921-1602-8/41	2941-1602-8/41	61 ¹ / ₂	38	43	330	410
2332-41/2- -- 125	2921-1602-8/41	2941-1602-8/41	61 ¹ / ₂	38	43	330	410
2338-41/2- -- 100	2921-1602-6/41	2941-1602-6/41	61 ¹ / ₂	38	43	310	390
50 hertz Direct Drive Blower							
23085-41/1- -- 25	2921-1602-6/41	2941-1602-6/41	50 ³ / ₄	38	43	310	390

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it