

Ordering Information | 1008A Valve

HOW TO ORDER

Valve Series	(A) Pipe Code	(B) Options
1008A	-02 3/8"	Blank standard
1008AU*	-01 1/2"	R reverse acting
	-0 3/4"	S steam service
	-1 1"	L NEMA 4 low fire switch
	-2 1 1/4"	LD manual locking device
	-3 1 1/2"	LDL manual locking device and NEMA 4 low fire switch
	-4 2"	B direct acting Beck 31 Series
	-5F 2 1/2"	Q 1199 direct acting valve
	-6F 3"	RK valve repair kit
	-7F 4"	
	-8F 6"	

* Valve with u-bracket for side-by-side combo

Valve Series	(C) Pipe Code	(B) Options
1010A	-02 3/8"	Blank standard
	-01 1/2"	S steam service
	-0 3/4"	Q 1199 direct acting valve
	-1 1"	
	-2 1 1/4"	
	-3 1 1/2"	
	-4 2"	
	-5 2 1/2"	
	-6 3"	

Examples:

- 1008A-5F-R 2 1/2" adjustable port valve reverse acting
- 1008AU-4-LDL 2" adjustable port valve with U bracket manual locking device and low fire switch
- 1008A-8F 6" adjustable port valve

Companion slip-on flanges for the -5F, -6F, -7F, and -8F valves are 8767A-5-S, 8767A-6-S, 8767A-7-S, and 8767A-8-S respectively. These include 1 flange, 1 gasket, and hardware.

NOTE: you will have to order quantity of 2 to install new valve.

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com
T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it