

# North American Solenoid Valves for Various Applications

Sheet1400-5

## VALVES FOR HEATED #6 FUEL OIL

All valves are auxiliary piloted.

Dimensions (inches)

North American R- Number	NPT	Max. OPD	Max. Fluid Temp. F	C <sub>v</sub>	Enclosure Type	Body Mat.
R950-6187	1/2	230	366	5.6	*	Bronze
R950-6202	3/4	230	366	11	*	Bronze
R950-6210	1	145	366	19	*	Bronze
R950-6215	1 1/4	90	366	25	*	Bronze
R950-6220	1/2	60	366	45	*	Bronze
R950-6225	2	40	366	63	*	Bronze

## AUXILIARY PILOT FOR ABOVE VALVES

(UL listed and CSA certified)

Dimensions (inches)

North American R- Number	NPT
R950-6240	1/8

A size	B	C	D	E	F	Weight
1/2	7 3/16	7 3/16	7 3/16	2 1/2	1	2.6
3/4	7 1/2	8 1/16	7 1/2	3	1 1/4	2.9
1	7 13/16	8 1/2	7 3/4	3 1/2	1 1/2	3.7
1 1/4	8 1/2	9	8	4 5/16	2	4.6
1 1/2	8 13/16	9 5/8	8 1/2	4 3/4	2 3/8	6.2
2	9 13/16	10 1/4	8 13/16	6	2 3/4	7.7

