

# Static Pressure | Pressure Switches

For use with hard wired systems

Switch Designation	Service	Action Press. Rise	Range of Operating Pressures	Max Static psi	Max Ambient Temp F	Differential Pressure (Dead Band)	Switch Rating		Approvals	Enclosure	Notes
							120Vac (Amps)	240Vac (Amps)			
8757-PG70-153/P1	Air	SPDT1	1-30" wc	15,20 (6)	180	4" wc	15	8	UL	1	1,6
8757-PG72-804/P1	Air	DPDT2	1-30" wc	15,20 (6)	180	8" wc	5	5	UL	1	2,6
8757-PG70-153/P2	Air	SPDT1	0.5-5 psi	15,20 (6)	180	0.5 psi	15	8	UL	1	1,6
8757-PG72-804/P2	Air	DPDT2	0.5-5 psi	15,20 (6)	180	1 psi	5	5	UL	1	2,6
8757-H400-441	Air	SPDT1	0-10" wc	3,225 (6)	160	0.15-0.3" wc	15	15	FM, UL, CE	4X	1,6
8757-H400-442	Air	SPDT1	0-20" wc	3,225 (6)	160	0.2-0.5" wc	15	15	FM, UL, CE	4X	1,6
8757-H400-443	Air	SPDT1	0-80" wc	3,225 (6)	160	0.5-1.8" wc	15	15	FM, UL, CE	4X	1,6
8757-H400-453	Air	SPDT1	0-20 psi	20,225 (6)	160	0.05-0.2 psi	15	15	FM, UL, CE	4X	1,6
8757-H400-454	Air	SPDT1	0-30 psi	30,225 (6)	160	0.05-0.3 psi	15	15	FM, UL, CE	4X	1,6
8757-DSF-7231/4	Air	SPDT1	1-35 psi	35	180	1.5 psi	15	15	FM, UL, CSA	1	1,3
8757-DSF-7231/7	Air	SPDT1	5-150 psi	150	180	3 psi	15	15	FM, UL, CSA	1	1,3
8757-12NNCA4	Air	SPDT1	0.5-6 psi	200,400 (6)	180	0.4 psi	22	22	FM	4X	1,6
8757-12NNCA45	Air	SPDT1	1-16 psi	200,400 (6)	180	0.6 psi	22	22	FM	4X	1,6
8757-4NNCA4	Air	SPDT1	2-25 psi	750,1000 (6)	180	1.2 psi	22	22	FM	4X	1,6
8757-4NNCA5	Air	SPDT1	3-50 psi	750,1000 (6)	180	1.6 psi	22	22	FM	4X	1,6
8757-4NNCA45	Air	SPDT1	4-75 psi	750,1000 (6)	180	2.0 psi	22	22	FM	4X	1,6
8757-6NNCA3	Air	SPDT1	12-100 psi	1500,2500 (6)	180	3.6 psi	22	22	FM	4X	1,6
8757-6NNCA5	Air	SPDT1	20-180 psi	1500,2500 (6)	180	5.6 psi	22	22	FM	4X	1,6
8757-GAO-A4/4/2	Gas, Air	SPDT1	0.16-1.2" wc	7	140	0.12" wc	10	5	FM, UL, CSA	4	1,3
8757-DG-2I	Gas, Air	SPDT1	0.2-2.4" wc	8.5	176	0.08-0.12" wc	5	5	FM, UL	IP65	1,3
8757-DG-4I	Gas, Air	SPDT1	0.4-4.0" wc	8.5	176	0.1-0.16" wc	5	5	FM, UL	IP65	1,3
8757-GAO-A4/4/3	Gas, Air	SPDT1	0.4-4.0" wc	7	140	0.2" wc	10	5	FM, UL, CSA	4	1,3
8757-GAO-A4/4/5	Gas, Air	SPDT1	2-20" wc	7	140	0.4" wc	10	5	FM, UL, CSA	4	1,3
8757-DG-20I	Gas, Air	SPDT1	1-20" wc	8.5	176	0.31-0.59" wc	5	5	FM, UL	IP65	1,3
8757-GML-A4/4/4	Gas, Air	SPDT1	1-20" wc	7	140	0.4" wc	10	5	FM, UL, CSA	4	1,3,7
8757-GAO-A4/4/6	Gas, Air	SPDT1	12-60" wc	7	140	1.2" wc	10	5	FM, UL, CSA	4	1,3
8757-DG-60I	Gas, Air	SPDT1	12-60" wc	8.5	176	1.17-1.95" wc	5	5	FM, UL	IP65	1,3
8757-GML-A4/4/6	Gas, Air	SPDT1	12-60" wc	7	140	1.2" wc	10	5	FM, UL, CSA	4	1,3,7
8757-GMH-A4/4/6	Gas, Air	SPDT1	12-60" wc	7	140	1.2" wc	10	5	FM, UL, CSA	4	1,3,7
8757-GAO-A4/4/8	Gas, Air	SPDT1	40-200" wc	14	140	4.0" wc	10	5	FM, UL, CSA	4	1,3
8757-DG-200I	Gas, Air	SPDT1	40-200" wc	8.5	176	3.12-6.63" wc	5	5	FM, UL	IP65	1,3
8757-12-20I	Gas, Air, Oil	SPDT1	-20-20" wc	75, 100 (6)	203	0.5-3.5" wc	5	5	CE,ANSI/ISA 12.27.01 UL, cUL	4X,Class I,II Div. I, II	1,5,6,9
8757-D4-30I	Gas, Air, Oil	SPDT1	4.5-30" wc	40,160 (6)	150	1.5-2.5" wc	15	15	FM, UL, CE	4X	1,5,6,8,9
8757-12-50I	Gas, Air, Oil	SPDT1	2-50" wc	75, 100 (6)	203	0.5-5" wc	5	5	CE, ANSI/ISA UL, cUL	4X,Class I,II	1,5,6,9
8757-D4-60I	Gas, Air, Oil	SPDT1	9-60" wc	40,160 (6)	150	1.5-3.5" wc	15	15	FM, UL, CE	4X	1,5,6,8,9
8757-D4-100I	Gas, Air, Oil	SPDT1	15-100" wc	40,160 (6)	150	2.5-5.5" wc	15	15	FM, UL, CE	4X	1,5,6,8,9
8757-D4-150I	Gas, Air, Oil	SPDT1	22.5-150" wc	40,160 (6)	150	4.5-8.5" wc	15	15	FM, UL, CE	4X	1,5,6,8,9
8757-12-200I	Gas, Air, Oil	SPDT1	10-200" wc	75, 100 (6)	203	1-10" wc	5	5	CE,ANSI/ISA 12.27.01 UL, cUL	4X,Class I,II Div. I, II	1,5,6,9
8757-12-15P	Gas, Air, Oil	SPDT1	1-15 psi	300,500 (6)	203	0.5-2.0 psi	5	5	CE,ANSI/ISA 12.27.01 UL, cUL	4X,Class I,II Div. I, II	1,5,6,9

(see page 4 for additional information)