Product Overview | 8775 & 8778AQuick Disconnects

- **Double automatic bleed-off valve built into both couplings that will enable you to connect against trapped static pressures.**
- **All steel couplings are zinc yellow dichromate plated with viton gaskets.**
- **Temperature rating (-20° to 375°) F**

*larger sizes available up to 4" **without built in bleed off valve.** (for liquid use only).
Please consult North American for pricing and information.

Part Number	Size*	Max Working Pressure (PSIG)	CV Factor
8775-02	⅜"	4500	.98
8775-01	½"	4000	2.5
8775-0	¾"	3500	4.6
8775-1	1"	2000	7.2

DIMENSIONS SHOWN ARE SUBJECT TO CHANGE. PLEASE OBTAIN CERTIFIED PRINTS FROM FIVES NORTH AMERICAN COMBUSTION, INC. IF SPACE LIMITATIONS OR OTHER CONSIDERATIONS MAKE EXACT DIMENSION(S) CRITICAL.

8778A PIPE COUPLINGS FOR HIGH OR LOW PRESSURE AIR OR NATURAL GAS

FEATURES

- **The 8778A pipe couplings are designed to simplify installation and ensure a tight seal with a push on gasket.**
- **They can be used to connect steel piping with diameters (½" through 4").**
- **Resistant to natural gas, natural gas odorants, carbon dioxide, water, and UV light.**
- **The coupling sleeve material is steel with an epoxy coating.**
- **Gasket material is buna nitrile.**
- **Temperature rating (-20° to 170°) F.**

Part Number	Size	Followers (Epoxy Coated)	Nuts & Bolts	Max Working Pressure (PSIG)
8778A-01	½"	Ductile Iron	½"	150
877A-0	¾"	Ductile Iron	½"	150
8778A-1	1"	Ductile Iron	½"	150
8778A-2	1¼"	Ductile Iron	½"	150
8778A-3	1½"	Ductile Iron	½"	150
8778A-4	2"	Steel	⅝"	400
8778A-5	2½"	Steel	⅝"	400
8778A-6	3"	Steel	⅝"	400
8778A-7	4"	Steel	⅝"	400