

MISCELLANEOUS AND ACCESSORIES (CONT'D)

TABLE 36 - ELECTRICAL CONNECTORS

DESCRIPTION	YORK P/N
Flow Sensor, (Style H)	025-41573-000
Hot Gas Bypass Valve Actuator- DIN Connector	025-37877-000
Oil Return Solenoid- DIN Connector	025-37876-000
Thrust Bearing Proximity Probe- DIN Connector	025-37805-000
Compressor Stall Sensor- DIN Connector	025-37805-000
Liquid Refrigerant level Sensor- DIN Connector	025-37805-000
PRV Actuator Connector	025-38172-000
VGD Actuator Connector	025-38172-000

TABLE 37 - RECOMMENDED SPARES

ITEM	DESCRIPTION	PART NUMBER
1	Preventive Maintenance Kit (YK G Unit)	366-94952-016
	Element Oil Filter	026-32831-000
	O-Ring Neo1 03.484ld .139Thk M (Oil Filter)	028-14404-000
	Filter Drier 3/8 Orfs	026-37563-000
	O-Ring Neo1 00.364ld .070Thk M (Filter Drier)	028-12961-012
2	Type K Oil (R-134a Units), 5 Gallons	011-00533-000
	Type K Oil (R-134a Units), 1 Gallon	011-01202-000
	Type K Oil (R-134a Units), 6 1-Gallons	011-00947-000

NOTE: Reference SI0135 for more information on recommended oil viscosities for R-134a single stage compressors.