

TABLE 4 – SERVICE AIDS

GASKET KIT**			VALVE RETAINING CLIP	BEARING REMOVAL TOOL	ROTOR MANDREL*	STATOR REMOVAL TOOL
COMPRESSOR MODEL						
4 CYLINDER	6 CYLINDER	8 CYLINDER				
364-48642	364-48643	364-48644	064-37274	364-37260	364-37273	029-13597

* Screws Into End of Crankshaft to Aid in Removing / Installing Rotor

** Depending on application, not all gaskets may be required.

TOP HEAD “VALVE REPLACEMENT” KITS & TOP HEAD “OVERHAUL” KITS

The price of the kits shown below is less than the total price of the individual parts. These kits provide a convenient, economical method of ordering replacement parts.

Each Top Head “Valve Replacement” Kit listed in Table 5 contains the suction and discharge valves, springs, gaskets, screws and nuts that are recommended to be replaced when a valve replacement is required.

Each Top Head “Overhaul” Kit listed in Table 6 contains the suction valves, suction springs, suction valve plates, discharge valve cage assemblies, gaskets, bolts and lockwashers that are recommended to be replaced when a top head overhaul is necessary.

Each kit has all of the recommended parts to service the valves located under one head for each compressor listed.

Included with each kit is a table of threaded torque values.

If servicing a complete compressor, order the Quantities listed in the Table.

Helical coil valve spring replacement must be done after every 5000 hours of running time on both suction and discharge valve assemblies.

R-22

TABLE 5 – TOP HEAD “VALVE REPLACEMENT” KIT

KIT PART NO. EACH KIT CONTAINS	R-22 364-47667-015		
	NO. OF KITS REQUIRED PER COMPRESSOR		
	4 CYL	6 CYL	8 CYL
Suction Valve	2	3	4
Discharge Valve			
Suction Valve Springs			
Discharge Valve Springs			
Top Head Gasket			
Discharge Manifold Gasket			

R-22

TABLE 6 – TOP HEAD “OVERHAUL” KIT

KIT PART NO. EACH KIT CONTAINS	R-22 364-47666-021		
	NO. OF KITS REQUIRED PER COMPRESSOR		
	4 CYL	6 CYL	8 CYL
Suction Valve, Plate & Spgs.	2	3	4
Dschg. Valve Cage Assmby			
Top Head Gasket			
Discharge Manifold Gasket			

* R-134a – 364-47666-020

* R-134a – Order parts separately. See page 9.

YORK OIL

Mineral Oil, R-22, Type C, 5-gallon can – 011-00312-000

POE Oil, R-134a, R-407c, Type H, 5-gallon can – 011-00549-000