

**TABLE 89 - VIBRATION ISOLATORS PART NUMBERS**

<b>NEOPRENE ISOLATOR CROSS REFERENCE (PIN 54 = N)</b>				
<b>**WEIGHT RANGE (LBS.)</b>	<b>WEIGHT RANGE (KG.)</b>	<b>MODEL PART NUMBER</b>	<b>COLOR</b>	<b>PART NUMBER</b>
Up to 826 lbs.	Up to 375 kg.	RD-3	CHARCOAL	029-25335-001
826 to 1689 lbs.	375 to 766 kg.	RD-4	BRICK RED	029-25335-002
1689 to ***4000 lbs.	766 to 1814 kg.	RD-4	CHARCOAL	029-25335-004
<b>ONE INCH DEFLECTION SPRING ISOLATOR CROSS REFERENCE* (PIN 54 = 1) SEE NOTE BELOW</b>				
<b>*WEIGHT RANGE (LBS.)</b>	<b>WEIGHT RANGE (KG.)</b>	<b>MODEL PART NUMBER</b>	<b>COLOR</b>	<b>PART NUMBER</b>
Up to 435 lbs.	Up to 197 kg.	CP-1D-510	BLACK	029-25334-002
435 to 766 lbs.	197 to 347 kg.	CP-1D-900	DARK GREEN	029-25334-003
766 to 1021 lbs.	347 to 463 kg.	CP-1D-1200	GRAY	029-25334-004
1021 to 1157 lbs.	463 to 525 kg.	CP-1D-1360	WHITE	029-25334-005
1157 to ***1785 lbs.	525 to 810 kg.	CP-1D-1785N	GRAY/RED	029-25334-006
Up to 1149 lbs.	Up to 521 kg.	C2P-1D-1350	DARK PURPLE	029-25334-008
1149 to 1531 lbs.	521 to 694 kg.	C2P-1D-1800	DARK GREEN	029-25334-009
1531 to 2041 lbs.	694 to 926 kg.	C2P-1D-2400	GRAY	029-25334-010
2041 to 2313 lbs.	926 to 1049 kg.	C2P-1D-2720	WHITE	029-25334-012
2313 to ***3570 lbs.	1049 to 1619 kg.	C2P-1D-3570N	GRAY/ RED	029-25334-013
<b>TWO INCH DEFLECTION, SEISMIC SPRING ISOLATOR CROSS REFERENCE (PIN 54 = S)</b>				
<b>*WEIGHT RANGE (LBS.)</b>	<b>WEIGHT RANGE (KG.)</b>	<b>MODEL PART NUMBER</b>	<b>COLOR</b>	<b>PART NUMBER</b>
Up to 392 lbs.	Up to 178 kg.	Y2RSI-2D-460	GREEN	029-25336-006
392 to 605 lbs.	178 to 274 kg.	Y2RSI-2D-710	DARK BROWN	029-25336-008
605 to 741 lbs.	274 to 336 kg.	Y2RSI-2D-870	RED	029-25336-009
741 to 1021 lbs.	336 to 463 kg.	Y2RSI-2D-1200N	RED/BLACK	029-25336-010
1021 to 1438 lbs.	463 to 652 kg.	Y2RSI-2D-1690	PINK	029-25336-011
1438 to 2245 lbs.	652 to 1018 kg.	Y2RSI-2D-2640N	PINK/GRAY	029-25336-012
2245 to 2619 lbs.	1018 to 1188 kg.	Y2RSI-2D-2870N	PINK/GRAY/ORANGE	029-25336-013
2619 to ***3740 lbs.	1188 to 1697 kg.	Y2RSI-2D-3280N	PINK/GRAY/DARK BROWN	029-25336-014

\* Value is de-rated by 15%.

\*\* Value is de-rated by 25%.

\*\*\* Value is not de-rated.

Note: One Inch Deflection Spring Isolators must all be of the same class for the entire unit.  
 Must use C2P's at all locations on a selected unit, or all CP's.